



**SUGGESTED CURRENT TRANSFORMER (CT)
RATIO TO SIZE CHART**

SOLID CORE

<u>RATIO</u>	<u>FOR USE WITH CABLE</u>	<u>FOR USE WITH BUS BAR</u>
100	10252ARW or 15352ARW	
200	10252ARW or 15352ARW	
400	15352ARW	
600	2547ARW or 25472SH	RT2052
800	3360RW or 4270RW	RT2052
1000	4270RW	RT2052 or RT3775
1500	4270RW	RT2052 or RT3775
1600	4270RW or 57902SH	RT2052 or RT3775
2000	57902SH	RT3775
2500	57902SH or 6291SH	RT3775
3000	6291SH or 8111SH	RT3775 or RT4011
4000	6291SH or 8111SH	RT3775 or RT4011

SPLIT CORE

<u>RATIO</u>	<u>FOR USE WITH CABLE</u>	<u>FOR USE WITH BUS BAR</u>
100		
200	1.5FSH	
400	1.5FSH or 2.5FSH	
600	3FSH	2052FSH
800	3FSH or 4FSH	2052FSH
1000	4FSH	2052FSH
1500	4FSH or 6FSH	2052FSH
1600	4FSH or 6FSH	2052FSH or 3775FSH
2000	4FSH or 6FSH	2052FSH or 3775FSH
2500	6FSH	2052FSH or 3775FSH
3000	6FSH or 8FSH	3775FSH or 4011FSH
4000	6FSH or 8FSH	3775FSH or 4011FSH