



Warranty: Free replacement on defective materials & workmanship for 1 year from date of shipment

Model	120vac Freq (HZ)	Air (CFM)	Volume (M ³ / MIN)	Current (A)	Power (W)	Speed (RPM)	Static Pressure (Inch - H ₂ O)	Noise (dBA)
FP-108X-KIT 119 x 119 x 25.4 mm	50 / 60	64 / 80	1.8 / 2.3	.19 / .18	14 / 16	2000 / 2350	.20 / .23	42 / 44
FP-108EXM-KIT 172 x 150 x 38 mm	50 / 60	205 / 230	5.8 / 6.5	0.4	30 / 28	2700 / 2900	.75 / .60	49
FP-108K-KIT 220 x 60 mm	50 / 60	360	10.2	0.7	52	2400	0.9	56

Ball Bearing, UL 94V-0 plastic with fiber glass impeller, die cast aluminium housing, shaded pole, impedance protected motor with terminal & wire leads. - **KIT includes louver**
Other (50-60Hz) Voltages Available: 24v, 48v, 100v, 220v, 240v, 380v

FP-108M/DC-KIT 119 x 119 x 25.4 mm	24vdc	88	2.5	0.24	5.76	3000	0.2	45
FP-108EX/DC-KIT 172 x 150 x 38 mm	24vdc	290	8.3	1.2	28.8	3400	0.78	63

Ball Bearing, UL 94V-0 plastic with fiber glass impeller & housing, brushless DC motor with terminal & wire leads. - **KIT includes louver**
Other Voltages Available: 12vdc, 48vdc



Plastic Louver / Vent	
SF-8803	148.5mm x 148.5mm x 13.5mm (for 120mm fan) IP44 / IP54
SF-8804	204mm x 204mm x 13.5mm (for 120mm / 150mm / 172mm fan) IP44 / IP54
SF-8805	255mm x 255mm x 13.5mm (for 172.5mm / 180mm / 200mm fan) IP44 / IP54
SF-8806	320mm x 320mm x 13.5mm (for 172.5mm / 180mm / 200mm / 220mm fan) IP44 / IP54

S.E.S.
Electric Sales
Phone (847) 364-3605
Fax (847) 364-4107



seselectricsales.com

Manufacturer Representatives