

DIN Mount Miniature Circuit Breakers

- * Holds 100% rated current independent of ambient temperature
- * Immediate resetting after trip (no cooling down time is necessary)
- * UL1077 and UL 508 approved for manual motor starting
- * Trips at 125% of rated current
- * Compact 13 mm width
- * Dual Mounting (DIN & Mini)

Current	Curve	1 pole	2 pole	3 pole
1 Amp	2	WCB-1P-2-1	WCB-2P-2-1	WCB-3P-2-1
	9	WCB-1P-9-1	WCB-2P-9-1	WCB-3P-9-1
2 Amp	2	WCB-1P-2-2	WCB-2P-2-2	WCB-3P-2-2
	9	WCB-1P-9-2	WCB-2P-9-2	WCB-3P-9-2
5 Amp	2	WCB-1P-2-5	WCB-2P-2-5	WCB-3P-2-5
	9	WCB-1P-9-5	WCB-2P-9-5	WCB-3P-9-5
10 Amp	2	WCB-1P-2-10	WCB-2P-2-10	WCB-3P-2-10
	9	WCB-1P-9-10	WCB-2P-9-10	WCB-3P-9-10
15 Amp	2	WCB-1P-2-15	WCB-2P-2-15	WCB-3P-2-15
	9	WCB-1P-9-15	WCB-2P-9-15	WCB-3P-9-15
20 Amp	2	WCB-1P-2-20	WCB-2P-2-20	WCB-3P-2-20
	9	WCB-1P-9-20	WCB-2P-9-20	WCB-3P-9-20
25 Amp	2	WCB-1P-2-25	WCB-2P-2-25	WCB-3P-2-25
	9	WCB-1P-9-25	WCB-2P-9-25	WCB-3P-9-25
30 Amp	2	WCB-1P-2-30	WCB-2P-2-30	WCB-3P-2-30
	9	WCB-1P-9-30	WCB-2P-9-30	WCB-3P-9-30
35 Amp	2	WCB-1P-2-35	WCB-2P-2-35	WCB-3P-2-35
	9	WCB-1P-9-35	WCB-2P-9-35	WCB-3P-9-35
40 Amp	2	WCB-1P-2-40	WCB-2P-2-40	WCB-3P-2-40
	9	WCB-1P-9-40	WCB-2P-9-40	WCB-3P-9-40
50 Amp	2	WCB-1P-2-50	WCB-2P-2-50	WCB-3P-2-50
	9	WCB-1P-9-50	WCB-2P-9-50	WCB-3P-9-50
60 Amp	2	WCB-1P-2-60	WCB-2P-2-60	WCB-3P-2-60
	9	WCB-1P-9-60	WCB-2P-9-60	WCB-3P-9-60



Curve 2 - General purpose curve. Trip range: 5-10x rated current

Curve 9 - Used when there is rush current. Trip range: 8-12x rated current

DIN Mount Fuse Holders

Single and multi-pole types available with fusing indicator for mounting on DIN/EN rail. Fuse holders are made of self-extinguishable materials, have silver plated copper contacts and UL and CSA approvals.

Part #	Description	Std Pkg
WFH-1P-Mid	1 Pole Midget Fuse Holder	12
WFH-2P-Mid	2 Pole Midget Fuse Holder	6
WFH-3P-Mid	3 Pole Midget Fuse Holder	4
WFH-1P-Mid-Neon	1 Pole Midget Fuse Holder with neon indicator	12
WFH-2P-Mid-Neon	2 Pole Midget Fuse Holder with neon indicator	6
WFH-3P-Mid-Neon	3 Pole Midget Fuse Holder with neon indicator	4
WFH-1P-CC	1 Pole CC Fuse Holder	12
WFH-2P-CC	2 Pole CC Fuse Holder	6
WFH-3P-CC	3 Pole CC Fuse Holder	4
WFH-1P-CC-Neon	1 Pole CC Fuse Holder with neon indicator	12
WFH-2P-CC-Neon	2 Pole CC Fuse Holder with neon indicator	6
WFH-3P-CC-Neon	3 Pole CC Fuse Holder with neon indicator	4



AC Circuit Breaker

UL 489 KM Curve - Trip range: 5-10x rated current

Current	1 pole	2 pole	3 pole
1 Amp	WCB-1P-KM-1	WCB-2P-KM-1	WCB-3P-KM-1
2 Amp	WCB-1P-KM-2	WCB-2P-KM-2	WCB-3P-KM-2
4 Amp	WCB-1P-KM-4	WCB-2P-KM-4	WCB-3P-KM-4
5 Amp	WCB-1P-KM-5	WCB-2P-KM-5	WCB-3P-KM-5
10 Amp	WCB-1P-KM-10	WCB-2P-KM-10	WCB-3P-KM-10
15 Amp	WCB-1P-KM-15	WCB-2P-KM-15	WCB-3P-KM-15
20 Amp	WCB-1P-KM-20	WCB-2P-KM-20	WCB-3P-KM-20
25 Amp	WCB-1P-KM-25	WCB-2P-KM-25	WCB-3P-KM-25




- | | |
|---|--|
| <ul style="list-style-type: none"> * Max Voltage: 240V, 50/60 Hz * Hydraulic-Magnetic Technology * CSA, VDE, CE and CCC approved * Ultra Compact – 13mm width | <ul style="list-style-type: none"> * Interrupting Capacity: 10kA (1pole) 5kA(2,3pole) * Trip Indication with Mid-Trip Handle * Reset Immediately After Overload * DIN and Dual Rail Mounting |
|---|--|
- * 100% Rating Independent of Ambient Temperature

DC Circuit Breakers

- | | |
|--|---|
| <ul style="list-style-type: none"> * 1 & 2 pole, 80v DC * 0.1 – 63 Amps (1 pole), 0.1 – 50 Amps (2 pole), * Ultra Compact – 13mm Width * Approvals: UL 489A, VDE & CE * 100% Rating Capability Independent of Ambient Temperature | <ul style="list-style-type: none"> * 10kA Interrupting Capacity * Reset Immediately After Overload * Dual Mounting (DIN & Mini) * U2 Tripping curve |
|--|---|

Ordering Code: WCB - (1 or 2) P- U2- X (x = current 1-63 Amps)



QF Range Dual Mount 26mm GFCI Circuit Breaker

- * VC 8035
- * Energy limiting capability on both switch and circuit breaker versions
- * Switch version fitted with short circuit protection for additional safety
- * Top busbar design enables easier installation
- * Single pole plus switched neutral earth leakage protection
- * Trip Indication (mid trip handle position)
- * Sensitivity: 30 mA
- * Earth leakage protection for applications requiring high sensitivity
- * Surface and Mini Rail mounting options

QF17A30mA10AMP
QF17A30mA15AMP
QF17A30mA20AMP
QF17A30mA25AMP
QF17A30mA30AMP
QF17A30mA35AMP
QF17A30mA40AMP
QF17A30mA50AMP
QF17A30mA60AMP
QF17A30mA63AMP



S.E.S.

Electric Sales

Phone (847) 364-3605
Fax (847) 364-4107



Manufacturer Representatives

seselectricsales.com