

Air Conditioner Product Line



HC = High Capacity Series
 CS = Compact Design Series
 NE = Narrow Edge 12" Wide Series
 WF = Wide Format Design Series

- All units are available in NEMA Type 12, 4 and 4X
- NEMA 4X available in 304 (2 finishes) and 316
- Hazardous Location Systems available for Class 1, Div 2, Groups B, C, D

AIR CONDITIONER PRODUCTS - GROUPED BY BTU/H

1Ø Model #	BTUs / HR	Voltage / Hz	Running Amps	Max Ambient °F	Max Integrated Heat in Watts	H x W x D	Ship Wt
CS011126	1000 - 2000	120v 60hz	2.7	125°F	350	17" x 7" x 7"	43
NE010126	1000	120v 60hz	3.44	125°F	NA	22" x 11.8" x 8.5"	57
NE010236	1000	230v 60hz	2.06	125°F	NA	22" x 11.8" x 8.5"	57
NE015126	1500	120v 60hz	3.49	125°F	NA	22" x 11.8" x 8.5"	57
NE015236	1500	230v 60hz	2.06	125°F	NA	22" x 11.8" x 8.5"	57
NE020126	2000	120v 60hz	3.76	131°F	1000	32" x 11.8" x 9.5"	70
NE020486	2000	480v 60hz	1.8	131°F	1000	37.71" x 11.8" x 9.5"	110
CS020126	2000	120v 60hz	3.76	125°F	500	20" x 10" x 10"	60
CS020236	2000	230v 60hz	2.1	125°F	500	20" x 10" x 10"	60
NE030126	3000	120v 60hz	5.15	131°F	1000	32" x 11.8" x 9.5"	70
NE030486	3000	480v 60hz	1.4	131°F	1000	37.71" x 11.8" x 9.5"	110
NE040126	4000	120v 60hz	5.53	131°F	1000	32" x 11.8" x 9.5"	70
NE040236	4000	230v 60hz	3.26	125°F	1000	32" x 11.8" x 9.5"	70
NE040486	4000	480v 60hz	1.7	125°F	1000	37.71" x 11.8" x 9.5"	110
NE050126	5000	120v 60hz	7.7	125°F	1000	36" x 11.8" x 15.1"	100
NE050236	5000	230v 60hz	4.07	125°F	1000	36" x 11.8" x 15.1"	100
NE050486	5000	480v 60hz	2.1	125°F	1000	44.63" x 11.8" x 15.1"	140
NE060126	6000	120v 60hz	7.83	125°F	1000	36" x 11.8" x 15.1"	100
NE060236	6000	230v 60hz	4.95	125°F	1000	36" x 11.8" x 15.1"	100
NE060486	6000	480v 60hz	2.6	125°F	1000	44.63" x 11.8" x 15.1"	140
WF060126	6000	120v 60hz	13.3	125°F	1000	36.8" x 19" x 10.5"	100
WF060236	6000	230v 60hz	6.8	125°F	1000	36.8" x 19" x 10.5"	100
NE080126	8000	120v 60hz	8.7	125°F	1000	36" x 11.8" x 15.1"	100
NE080236	8000	230v 60hz	5.05	125°F	1000	36" x 11.8" x 15.1"	100
NE080486	8000	480v 60hz	2.8	125°F	1000	44.63" x 11.8" x 15.1"	140
WF080126	8000	120v 60hz	12.85	125°F	1000	36.8" x 19" x 10.5"	100
WF080236	8000	230v 60hz	9	125°F	1000	36.8" x 19" x 10.5"	100
HC100126	10,000	120v 60hz	16.3	125°F	1500	48" x 15.9" x 15.1"	145
HC100236	10,000	230v 60hz	8.12	125°F	1500	48" x 15.9" x 15.1"	145
HC100486	10,000	480v 60hz	4.5 approx	125°F	1500	57.63" x 15.9" x 15.1"	205
HC120126	12,000	120v 60hz	16.3	125°F	1500	48" x 15.9" x 15.1"	145
HC120236	12,000	230v 60hz	8.12	125°F	1500	48" x 15.9" x 15.1"	145
HC120486	12,000	480v 60hz	4.5 approx	125°F	1500	57.63" x 15.9" x 15.1"	205
HC155236	15,000	230v 60hz	8.41	125°F	1500	48" x 15.9" x 15.1"	145
HC155486	15,000	480v 60hz	4.8 approx	125°F	1500	57.63" x 15.9" x 15.1"	205
HC200236	20,000	230v 60hz	11.27	125°F	1500	56.1" x 23.4" x 15.2"	186
HC200486	20,000	480v 60hz	6.2 approx	125°F	1500	65.72" x 23.4" x 15.2"	235

Engineered & manufactured to endure the most difficult of environments and applications. Thermal Edge A/C units exceed environmental requirements in applications like Steel, Food Processing, Petro-Chemical, Cement, Paper & Pulp and Plastics. Available in NEMA types 12, 4 & 4X (304SS & 316SS)