



Thermal Edge Inc.

Powder Coated & Stainless Steel FILTER FAN PACKAGES

- * Includes 8' Cord w/Plug
- * Efficient, Quiet Ball Bearing Fans
- * Electrostatic Polypropylene Filter Media
- * 16ga Powder Coat or 304 Stainless Steel

Note: Each fan kit includes fan, (2) grilles, (2) filters, (2) gaskets, template & mounting hardware



Powder Coated Steel	Free Flow CFM	Voltage / Hz	Amps	Temp Range	RPM	Dimensions H x W x D
TEI-MFFP-100-120-1	131	115v 50/60Hz	0.18	-4°F to 176°F	3300	7.9" x 7.9" x 1.481"
TEI-MFFP-100-230-1		208v-230v 60Hz	0.1			
TEI-MFFP-100-D24-1	140	24vdc	0.58		3450	
TEI-MFFP-200-120-1	300	115v 50/60Hz	0.44			
TEI-MFFP-200-230-1		208v-230v 60Hz	0.23			
TEI-MFFP-200-D24-1		24vdc	1.42	-4°F to 167°F	3300	9.93" x 9.93" x 2.094"
TEI-MFFP-500-120-1	750	115v 50/60Hz	0.44	-4°F to 158°F		
TEI-MFFP-500-220-1		208v-230v 60Hz	0.23			
304 Stainless	Free Flow CFM	Voltage / Hz	Amps	Temp Range	RPM	Dimensions H x W x D
TEI-SFFP-200-120-1	300	115v 50/60Hz	0.44	-4°F to 167°F	3300	7.9" x 7.9" x 1.481"
TEI-SFFP-200-230-1		208v-230v 60Hz	0.23			
TEI-SFFP-200-D24-1		24vdc	1.42			



DIN Rail Thermostats

01140.9-00	32° - 140°F	NC - opens on temp rise
01141.9-00	32° - 140°F	NO - close on temp rise
01146.9-00	0°-60°C	NC - opens on temp rise
01147.9-00	0°-60°C	NO - close on temp rise
01157.0-00	-15° to +45°C	NC - opens on temp rise



3R Rain Shrouds (2 per kit)

Powder Coat Steel	Dimensions H x W x D
100FFP-3R	8.38" x 9.48" x 6.13"
200FFP-3R	10.38" x 10.13" x 7.46"
500FFP-3R	15.06" x 14.31" x 10.13"