



Thermal Edge Inc.

Injection Molded Plastic FILTER FAN PACKAGES

- * Fastener Hardware or Snap Mount
- * Efficient, Quiet Ball Bearing Fans
- * Electrostatic Polypropylene Filter Media

Note: Each fan kit includes fan, (2) grilles, (2) filters, (2) gaskets, template & mounting hardware



Model	Free Flow CFM	Voltage / Hz	Amps	Temp Range	RPM	Dimensions H x W x D
TEI-PFFP-080-126	80	115v 50/60Hz	0.11	-4°F to 176°F	2900	5.86" x 5.86" x 2.26"
TEI-PFFP-080-236		208v 60Hz	0.06			
TEI-PFFP-080-24		24vdc	0.23			
TEI-PFFP-100-126	100	115v 50/60Hz	0.18		3300	8.03" x 8.03" x 3.15"
TEI-PFFP-100-236		208v 60Hz	0.1			
TEI-PFFP-100-24		24vdc	0.58			
TEI-PFFP-200-126	200	115v 50/60Hz	0.44	3300	10.06" x 10" x 3.87"	
TEI-PFFP-200-236		208v 60Hz	0.23			
TEI-PFFP-200-24		24vdc	1.42			
TEI-PFFP-390-126	390	115v 50/60Hz		-4°F to 176°F	3450	12.6" x 12.6" x 4.33"
TEI-PFFP-390-236		208v 60Hz				
TEI-PFFP-390-24		24vdc				
TEI-PFFP-500-126	500	115v 50/60Hz	0.44	-4°F to 158°F	2200	7.12" x 16.56" x 2.26"
TEI-PFFP-500-236		208v 60Hz	0.23			



DIN Rail Thermostats

01140.9-00	32° - 140°F	NC - opens on temp rise
01141.9-00	32° - 140°F	NO - close on temp rise
01146.9-00	0°-60°C	NC - opens on temp rise
01147.9-00	0°-60°C	NO - close on temp rise
01157.0-00	-15° to +45°C	NC - opens on temp rise



3R Rain Shrouds (2 per kit)

Powder Coat Steel	Dimensions H x W x D
100FFP-3R	8.38" x 9.48" x 6.13"
200FFP-3R	10.38" x 10.13" x 7.46"
500FFP-3R	15.06" x 14.31" x 10.13"