



FP-108X-KIT
80 CFM Freeflow
156 x 156 x 56mm



FP-108EXM-KIT
230 CFM Freeflow
207 x 207 x 86mm



FP-108K-KIT
360 CFM Freeflow
322 x 322 x 108mm



Warranty: Free replacement on defective materials & workmanship for 1 year from date of shipment

Model	120vac Freq (HZ)	Air (CFM)	Volume (M ³ / MIN)	Current (A)	Power (W)	Speed (RPM)	Static Pressure (Inch - H ₂ O)	Noise (dBA)
FP-108X-KIT 119 x 119 x 25.4 mm	50 / 60	64 / 80	1.8 / 2.3	.19 / .18	14 / 16	2000 / 2350	.20 / .23	42 / 44
FP-108EXM-KIT 172 x 150 x 38 mm	50 / 60	205 / 230	5.8 / 6.5	0.4	30 / 28	2700 / 2900	.75 / .60	49
FP-108K-KIT 220 x 60 mm	50 / 60	360	10.2	0.7	52	2400	0.9	56

Ball Bearing, UL 94V-0 plastic with fiber glass impeller, die cast aluminium housing, shaded pole, impedance protected motor with terminal & wire leads. - **KIT includes louver**

Other (50-60Hz) Voltages Available: 24v, 48v, 100v, 220v, 240v, 380v

FP-108M/DC-KIT 119 x 119 x 25.4 mm	24vdc	88	2.5	0.24	5.76	3000	0.20	45
FP-108/DC-KIT 119 x 119 x 38 mm	24vdc	105	3.0	0.36	8.60	3000	0.78	45

Ball Bearing, UL 94V-0 plastic with fiber glass impeller & housing, brushless DC motor with terminal & wire leads. - **KIT includes louver**

Other Voltages Available: 12vdc, 48vdc



Plastic Louver / Vent

SF-8803X	156mm x156mm x 17mm (for 120mm fan) IP44 / IP54
SF-8804X	207mm x 207mm x 24mm (for 120mm / 150mm / 172mm fan) IP44 / IP54
SF-8806X	322mm x 322mm x 24mm (for 172.5mm / 180mm / 200mm / 220mm fan) IP44 / IP54